

Series: HRLSD-SPO, HRLSD-GTH

Welded steel heavy duty levelling castors with adjustable mounting height, with top plate fitting

1100 - 1300 kg ✓RoHS



Brackets: HRLSD series - Especially robust welded steel construction with DIN 711 axial grooved ball bearing and DIN 720 tapered roller bearing in the swivel head, dust and splash-proof, with welded guide bushing for the exceedingly strong truck lock. The height of the wheels and the truck lock can be adjusted with an open-ended spanner (width across flats 24 mm). Bolted wheel axle. Zinc-plated, yellow-passivated, Cr6-free.

Wheels: SPO series - Made of high-quality, impact-resistant polyamide 6, very robust, heavy duty design, 70° Shore D, natural white.

GTH series - Tread: Made of high-quality polyurethane-elastomer Blickle Extrathane®, 92° Shore A, light brown, non-marking, non-staining. Wheel centre: Made of robust grey cast iron.

Bearing type: Two pressed-in ball bearings.



Swivel castors	Wheel Ø (D) [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height (H) [mm]	Max. total height (h) [mm]	Max foot floor clearance * [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset [mm]
SPO series											
HRLSD-SPO 125K	125	2 x 40	1300	Ball bearing	170	210	40	175 x 140	140 x 105	14	58-70
GTH series											
HRLSD-GTH 127K	125	2 x 50	1100	Ball bearing	170	210	40	175 x 140	140 x 105	14	58-70

* With screwed-in truck lock and screwed in adjustment screw

Options **



Illustration	SPO series	Electrically conductive version, non-marking grey
Product code suffix		-EL
Available for		SPO series on request

** More options: Further heavy duty designs on request

