


Series: LER-POES

**Pressed steel castors with bolt hole, wheel with "Blickle SoftMotion" soft rubber tyres**

150 kg

RoHS



**Brackets:** LER series – Made of pressed steel, with double ball bearing in the swivel head, strong central kingpin, ball protection by the special top plate and ball disc design. The special Blickle dynamic riveting process for the swivel head results in minimal swivel head play and smooth rolling characteristics with increased service life achieved by work hardening the ball race grooves. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

**Wheels:** POES series – Tyres: Made of "Blickle SoftMotion" high-quality elastic solid rubber, 55° shore A, grey, non-marking. Wheel centre: Made of high-quality, impact-resistant black polyamide 6. Bearing type: Centrally over-moulded ball bearing (C).



Swivel castors	Swivel castors with 'stop-fix' brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plates Ø [mm]	Bolt hole Ø [mm]	Offset [mm]
LER-POES 100K-SG	LER-POES 100K-FI-SG	100	40	150	Ball bearing (C)	125	70	13	36
LER-POES 125K-SG	LER-POES 125K-FI-SG	125	40	150	Ball bearing (C)	150	70	13	40

**Options**



	Light duty swivel castor with bolt hole	Light-duty fixed castor with bolt hole	Light-duty swivel castors with bolt hole and 'stop-fix' brake
<b>Product code suffix</b>	LKRA-POES 102K-SG-FK LKRA-POES 127K-SG-FK	BKRA-POES 102K-SG-FK BKRA-POES 127K-SG-FK	LKRA-POES 102K-FI-SG-FK LKRA-POES 127K-FI-SG-FK
<b>Available for</b>	All sizes	All sizes	All sizes