

Series: POEV...-SB, POEV...-SG

## Heavy-duty wheels with elastic solid rubber "Blickle EasyRoll" tyres with polyamide wheel centre

150 – 250 kg

RoHS



<b>Tread hardness</b>		65° Shore A
<b>Heat resistance</b>		-25° C - +80° C up to +100° C for short periods
<b>Rolling resistance</b>		Excellent
<b>Operating noise</b>		Excellent
<b>Floor surface preservation</b>		Excellent

**Blickle**  
EasyRoll

### POEV wheel series:

**Tyres:** Made of high-quality elastic solid rubber in "Blickle EasyRoll", 65° Shore A hardness, extremely high degree of operational comfort, low-noise rolling, minimal rolling resistance, extremely good floor protection, non-marking blue (-SB) or non-marking grey (-SG) vulcanised onto the wheel centre.

**Wheel centre:** Made of high-quality, impact-resistant black polyamide 6.

### Bearing type:

- Ball bearing (C): Centrally encapsulated, sealed ball bearing lubricated with long-life grease.

### Other characteristics:

High chemical resistance to many aggressive substances, except oils (G15 catalogue, Table on page 36-37).

Temperature resistance: -25° C to +80° C, up to +100° C for short periods.

At ambient temperatures above +35° C the load capacity is reduced.

Maintenance-free under normal conditions.

Wheels	Wheel Ø	Wheel width	Load capacity [kg]	Bearing type	Axle hole Ø	Hub length
	(D) [mm]	(T2) [mm]			(d) [mm]	(T1) [mm]
<b>POEV 102/8-36K-SB</b>	100	32	200	Ball bearing (C)	8	36
<b>POEV 102/8K-SB</b>	100	32	200	Ball bearing (C)	8	46
<b>POEV 102/8-36K-SG</b>	100	32	200	Ball bearing (C)	8	36
<b>POEV 102/8K-SG</b>	100	32	200	Ball bearing (C)	8	46
<b>POEV 127/8K-SG-01</b>	125	31	150	Ball bearing (C)	8	36
<b>POEV 126/8K-SB-01</b>	125	37	250	Ball bearing (C)	8	46
<b>POEV 126/10K-SB-01</b>	125	37	250	Ball bearing (C)	10	46
<b>POEV 126/8K-SG-01</b>	125	37	250	Ball bearing (C)	8	46
<b>POEV 126/10K-SG-01</b>	125	37	250	Ball bearing (C)	10	46

For additional wheelØ, see catalogue G15 page 164

For other variants, please refer to the full Blickle G15 catalogue!

### Options



	in an electrically conductive version, black tyre	Wheel with additional ball bearing seal
<b>Product code suffix</b>	<b>-EL</b>	<b>-KD</b>
Available for	On request	On request

